

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application.

### **Listing of Claims:**

Claim 1 (currently amended): A method of computer data analysis using neural networks, the method including:

generating a data representation using a data set, the data set including a plurality of attributes, wherein generating the data representation includes:

modifying the data set using a training algorithm, wherein the training algorithm includes growing the data set; ~~and~~

performing convergence testing, wherein convergence testing checks for convergence of the training algorithm; ~~and wherein~~

repeating the modification ~~ing~~ of the data set ~~is repeated~~ until convergence of the training algorithm occurs; and

displaying one or more subsets of the data set using the data representation.

Claim 2 (currently amended): A The method according to claim 1, further including generating the data set using input data, ~~and~~ wherein generating the data set includes formatting the input data, and initializing the formatted input data.

Claim 3 (currently amended): A The method according to claim 2, wherein formatting the input data further includes creating a container class including a list of data vectors,  $\bar{\mathbf{D}}$ , where  $\mathbf{d}_i$  is the  $i$ th vector in  $\bar{\mathbf{D}}$ , and  $\mathbf{d}_{i,j}$  is the  $j$ th element of vector  $i$ .

Claim 4 (currently amended): A The method according to claim 2, wherein formatting the input data further includes data scaling and binarisation of at least a portion of the data set.

Claim 5 (currently amended): A The method according to claim 4, wherein data scaling includes replacing each element in each data vector in the data set by a scaled representation of itself, where:

$$\forall i \in [1, \text{card}(\mathbf{d})], \forall \mathbf{d}_i \in \overline{\mathbf{D}}; \text{ and}$$

$$d_{i,j} = \frac{(d_{i,j} - i_{\min})}{(i_{\max} - i_{\min})}.$$

Claim 6 (currently amended): A The method according to claim 4 ~~or 5~~, wherein binarisation includes converting attributes into one or more toggled attribute values.

Claim 7 (currently amended): A The method according to claim 1 ~~any one of the preceding claims~~, wherein performing convergence testing includes testing condition  $q(t) < Q_e$ .

Claim 8 (currently amended): A The method according to claim ~~any one of claims 2 to 7~~, wherein initializing the formatted input data includes:

calculating an autocorrelation matrix,  $\aleph$  over the input data set  $\overline{\mathbf{D}}$ ,

$$\text{where } \aleph = \frac{1}{\text{card}(\overline{\mathbf{D}})} \sum_{\mathbf{d} \in \overline{\mathbf{D}}} \mathbf{d} \cdot \mathbf{d}^T;$$

finding two longest eigenvectors of  $\aleph$ ,  $\mathbf{e}_1$  and  $\mathbf{e}_2$ , where  $|\mathbf{e}_1| > |\mathbf{e}_2|$ ; and

initializing vector values of each element of the data set  $F$  by spanning it with element values of the eigenvectors.

Claim 9 (currently amended): A The method according to claim 8, wherein initializing the vector values includes:

$$F_{\langle F_R, 0 \rangle} := \mathbf{0};$$

$$F_{\langle F_R, F_C \rangle} := \mathbf{e}_1;$$

$$F_{\langle 1, F_C \rangle} := \mathbf{e}_1 + \mathbf{e}_2;$$

$$F_{\langle F_R, F_C \rangle} := \mathbf{e}_2;$$

$$\forall c \in [2, F_C - 1], F_{\langle 1, c \rangle} := \frac{F_C}{F_C - c} F_{\langle 1, F_C \rangle} + \frac{F_C - c}{F_C} F_{\langle 1, 1 \rangle};$$

$$\forall c \in [2, F_C - 1], F_{\langle R_C, c \rangle} := \frac{c}{F_C} F_{\langle F_R, F_C \rangle} + \frac{F_C - c}{F_C} F_{\langle F_R, 1 \rangle};$$

$$\forall r \in [2, F_R - 1], F_{\langle r, 1 \rangle} := \frac{c}{F_R} F_{\langle F_R, 1 \rangle} + \frac{F_R - r}{F_R} F_{\langle 1, 1 \rangle};$$

$$\forall r \in [2, F_R - 1], F_{\langle r, F_C \rangle} := \frac{r}{F_R} F_{\langle F_R, F_C \rangle} + \frac{F_R - r}{F_R} F_{\langle r, F_R \rangle}; \text{ and}$$

$$\forall r \in [2, F_R - 1], \forall c \in [2, F_C - 1], F_{\langle r, c \rangle} := \frac{c}{F_C} F_{\langle r, F_C \rangle} + \frac{F_C - c}{F_C} F_{\langle r, 1 \rangle}.$$

Claim 10 (currently amended): A The method according to ~~any one of the preceding~~ claims 1, wherein the data set includes a plurality of data set nodes, and wherein growing the data set includes:

finding  $K_q$  for each of the data set nodes, where  $K_q$  is the node with the highest average quantization error,  $\arg \max_q \{ \bar{q}(t)_{K_q} \}$  for each of the data set nodes,

where  $\bar{q}(t)_{K_q} = \frac{1}{t-1} \sum_{i=1}^{t-1} q(t)_{K_q}$  is the average quantization error for node  $q$ , where:

$$K_x = \arg \max_x \{ \|K_q - K_{\langle r(q)-1, c(q) \rangle} \|, \|K_q - K_{\langle r(q)+1, c(q) \rangle} \| \}$$

$$K_y = \arg \max_y \{ \|K_q - K_{\langle r(q), c(q)-1 \rangle} \|, \|K_q - K_{\langle r(q), c(q)+1 \rangle} \| \}$$

if  $\|K_y - K_c\| < \|K_x - K_c\|$  then

$n_r = r(y)$  if  $r(y) < r(c)$ , else  $n_r = r(c)$ ; and

$n_c = c(y)$ ;

else  $n_r = r(y)$ ;  $n_c = c(x)$  if  $c(x) < c(c)$ , else  $n_c = c(c)$ ;

inserting a new row and column after row  $n_r$  and column  $n_c$ ; and

interpolating new attribute values for the newly inserted node vectors using:

$$K_{\langle r, n_c \rangle} = (K_{\langle r, n_c-1 \rangle} + K_{\langle r, n_c+1 \rangle}) \frac{\alpha}{2} \text{ and } K_{\langle n_r, c \rangle} = (K_{\langle n_r-1, c \rangle} + K_{\langle n_r+1, c \rangle}) \frac{\alpha}{2}, \text{ where } \alpha \in U(0,1).$$

Claim 11 (currently amended): A The method according to ~~any one of the preceding~~ claims 1, wherein the training algorithm further includes:

$t = t + 1$ ;

$\forall \mathbf{d} \in \overline{\mathbf{D}}$ ;

if ( $t < 50$  or *afterGrow*)

$$\mathbf{d} = \arg \min_{\langle r, c \rangle, \forall r \in [1, F_R], \forall c \in [1, F_C]} \|\mathbf{d} - F_{\langle r, c \rangle}\|_{\rho}$$

*afterGrow* = *false*

else

$\mathbf{d} = \text{FindSCWS}(\mathbf{d})$

call function: *FindNeighborhoodPatterns*( $\overline{\phi}$ )

call function: *BatchUpdateMatchVectors*

$$q(t) = \frac{1}{\text{card}(\overline{\mathbf{D}})} \sum_i (\|\mathbf{d} - F_{\phi \mathbf{d}}\|_{\rho}); \text{ and}$$

if (*MayGrow*( $t$ ) and  $t < t_{\max}$ ), call function: *GrowKF*.

Claim 12 (currently amended): A The method according to ~~any one of the preceding~~ claims 1, wherein displaying one or more subsets of the data set includes:

using a composite view to view multiple attributes; and wherein

creating an additional attribute image ~~is created~~, wherein the additional attribute image displays ~~ing~~ a union of a selected set of attributes.

Claim 13 (currently amended): A The method according to claim 12, wherein using a composite view further includes:

constructing an attribute matrix; and

selecting a highest value for each attribute value from the selected set of attributes.

Claim 14 (currently amended): A The method according to ~~any one of the preceding~~ claims 1, wherein displaying one or more subsets of the data set includes using a range filter, wherein using the range filter includes:

- to selecting regions on the data representation; and
- filtering out nodes based on defined value ranges.

Claim 15 (currently amended): A The method according to ~~any one of the preceding~~ claims 1, wherein displaying one or more subsets of the data set includes using a zooming function, wherein using the zooming function includes:

- making a selection of nodes to form a base reference of interest;
- defining a set of data records from a second data set;
- matching the second data set to the data representation;
- flagging all records that are linked to the matched region; and
- generating a second data representation using the flagged records.

Claim 16 (currently amended): A The method according to ~~any one of the preceding~~ claims 1, wherein displaying one or more subsets of the data set includes:

- using visual scaling;
- changing the minimum and maximum values used to calculate a color progression used to visualize at least one of the plurality of attributes; and
- re-interpolating the active color ranges over the new valid range of attribute values.

Claim 17 (currently amended): ~~A~~ The method according to ~~any one of the preceding~~ claims 1, wherein displaying one or more subsets of the data set includes using a labeling engine, wherein using the labeling engine includes to:

- linking attribute columns in an input file to attributes in the data representation;
- selecting attributes from the input file to be used for labelling;
- determining with which row and column each row in the input file is associated;
- and
- placing labels on the data representation.

Claim 18 (currently amended): ~~A~~ The method according to ~~any one of the preceding~~ claims 1, wherein displaying one or more subsets of the data set includes using an advanced search function, wherein using the advanced search function includes to:

- reading a set of data records from a data source;
- matching attribute columns from the set of data records to attributes in the data representation; and
- displaying a list of all records that are associated with nodes that are part of the active selection on the data representation.

Claim 19 (currently amended): ~~A~~ The method according to ~~any one of the preceding~~ claims 1, wherein displaying one or more subsets of the data set includes using equal distance averaging (EDA), wherein using the equal distance averaging includes:

- finding the node vector,  $\mathbf{n}$ , in the data representation that most closely represents the input data vector,  $\mathbf{d}$ ; where  $\mathbf{n} = \arg \min_{K_{\langle r, c \rangle}} \left\{ \left\| K_{\langle r, c \rangle} - \mathbf{d} \right\|_{\rho} \right\}, \forall r \in [1, K_R], \forall c \in [1, K_C];$
- and
- replacing missing entries in  $\mathbf{d}$  with the corresponding entries from  $\mathbf{n}$ .

Claim 20 (currently amended): A The method according to claim 19, wherein using the equal distance averaging further includes:

building a list of the data representation nodes values,  $\overline{\mathbf{M}}$ , such that for each element  $\mathbf{m}$  of  $\overline{\mathbf{M}}$ ,  $\|\mathbf{m} - \mathbf{d}\|_\rho = 0$ ; wherein if  $\overline{\mathbf{M}}$  is empty, then replace each missing entry in  $\mathbf{d}$  with corresponding entries in  $\mathbf{n}$ ; and if  $\overline{\mathbf{M}}$  is not empty, then replace each missing entry in  $\mathbf{d}$  with the average value of the corresponding position of all the elements in  $\overline{\mathbf{M}}$ .

Claim 21 (currently amended): A The method according to ~~any one of the preceding~~ claims 1, wherein the data representation is a knowledge filter.



Claim 22 (currently amended): A method of computer data analysis using neural networks, the method including:

generating a data set,  $\overline{\mathbf{D}}$ , the data set including a plurality of attributes and a plurality of data set nodes;

initializing the data set, wherein initializing the data set includesing:

calculating an autocorrelation matrix,  $\aleph$  over the input data set  $\overline{\mathbf{D}}$ ,

$$\text{where } \aleph = \frac{1}{\text{card}(\overline{\mathbf{D}})} \sum_{\mathbf{d} \in \overline{\mathbf{D}}} \mathbf{d} \cdot \mathbf{d}^T ;$$

finding two longest eigenvectors of  $\aleph$ ,  $\mathbf{e}_1$  and  $\mathbf{e}_2$ , where  $|\mathbf{e}_1| > |\mathbf{e}_2|$ ; and

initializing vector values of each element of a data representation  $F$  by spanning it with element values of the eigenvectors;

generating a data representation using a training algorithm, wherein the training algorithm includes growing the data set, and wherein growing the data set includesing:

finding  $K_q$  for each of the data set nodes, where  $K_q$  is the node with the highest average quantization error,  $\arg \max_q \left\{ \overline{q}(t)_{K_q} \right\}$  for each of the data

set nodes, where  $\overline{q}(t)_{K_q} = \frac{1}{t-1} \sum_{i=1}^{t-1} q(t)_{K_q}$  is the average quantization error for node  $q$ , where:

$$K_x = \arg \max_x \left\{ \|K_q - K_{\langle r(q)-1, c(q) \rangle} \|, \|K_q - K_{\langle r(q)+1, c(q) \rangle} \| \right\}$$

$$K_y = \arg \max_y \left\{ \|K_q - K_{\langle r(q), c(q)-1 \rangle} \|, \|K_q - K_{\langle r(q), c(q)+1 \rangle} \| \right\}$$

if  $\|K_y - K_c\| < \|K_x - K_c\|$  then

$$n_r = r(y) \text{ if } r(y) < r(c), \text{ else } n_r = r(c); \text{ and}$$

$$n_c = c(y);$$

else  $n_r = r(y); n_c = c(x)$  if  $c(x) < c(c)$ , else  $n_c = c(c)$ ;

inserting a new row and column after row  $n_r$  and column  $n_c$ ; and

interpolating new attribute values for the newly inserted node vectors  
using:  $K_{\langle r, n_c \rangle} = \left( K_{\langle r, n_c - 1 \rangle} + K_{\langle r, n_c + 1 \rangle} \right) \frac{\alpha}{2}$  and  $K_{\langle n_r, c \rangle} = \left( K_{\langle n_r - 1, c \rangle} + K_{\langle n_r + 1, c \rangle} \right) \frac{\alpha}{2}$ , where  
 $\alpha \in U(0,1)$ ;

performing convergence testing, wherein convergence testing checks for  
convergence of the training algorithm; ~~and wherein~~

~~repeating the training algorithm is repeated~~ until convergence of the training  
algorithm occurs; and

displaying one or more subsets of the data set using the data representation.

Claim 23 (currently amended): A The method according to claim 22, wherein initializing  
the vector values further includes:

$$F_{\langle F_R, 0 \rangle} := \mathbf{0};$$

$$F_{\langle F_R, F_C \rangle} := \mathbf{e}_1;$$

$$F_{\langle 1, F_C \rangle} := \mathbf{e}_1 + \mathbf{e}_2;$$

$$F_{\langle F_R, F_C \rangle} := \mathbf{e}_2;$$

$$\forall c \in [2, F_C - 1], F_{\langle 1, c \rangle} := \frac{F_C}{F_C - c} F_{\langle 1, F_C \rangle} + \frac{F_C - c}{F_C} F_{\langle 1, 1 \rangle};$$

$$\forall c \in [2, F_C - 1], F_{\langle F_R, c \rangle} := \frac{c}{F_C} F_{\langle F_R, F_C \rangle} + \frac{F_C - c}{F_C} F_{\langle F_R, 1 \rangle};$$

$$\forall r \in [2, F_R - 1], F_{\langle r, 1 \rangle} := \frac{c}{F_R} F_{\langle F_R, 1 \rangle} + \frac{F_R - r}{F_R} F_{\langle 1, 1 \rangle};$$

$$\forall r \in [2, F_R - 1], F_{\langle r, F_C \rangle} := \frac{r}{F_R} F_{\langle F_R, F_C \rangle} + \frac{F_R - r}{F_R} F_{\langle r, F_R \rangle}; \text{ and}$$

$$\forall r \in [2, F_R - 1], \forall c \in [2, F_C - 1], F_{\langle r, c \rangle} := \frac{c}{F_C} F_{\langle r, F_C \rangle} + \frac{F_C - c}{F_C} F_{\langle r, 1 \rangle}.$$

Claim 24 (currently amended): ~~A~~ The method according to claim 22 ~~or 23~~, wherein the training algorithm further includes:

$t = t + 1;$

$\forall \mathbf{d} \in \overline{\mathbf{D}};$

if ( $t < 50$  or *afterGrow*)

$$\mathbf{d} = \arg \min_{\langle r, c \rangle, \forall r \in [1, F_R], \forall c \in [1, F_C]} \|\mathbf{d} - F_{\langle r, c \rangle}\|_{\rho}$$

*afterGrow* = *false*

else

$\mathbf{d} = \text{FindSCWS}(\mathbf{d})$

call function: *FindNeighborhoodPatterns*( $\overline{\rho}$ )

call function: *BatchUpdateMatchVectors*

$$q(t) = \frac{1}{\text{card}(\overline{\mathbf{D}})} \sum_i (\|\mathbf{d} - F_{\rho \mathbf{d}}\|_{\rho}); \text{ and}$$

if (*MayGrow*( $t$ ) and  $t < t_{\max}$ ), call function: *GrowKF*.

Claim 25 (currently amended): ~~A~~ The method according to claim 22, 23, ~~or 24~~, wherein performing convergence testing includes testing condition  $q(t) < Q_c$ .

Claim 26 (currently amended): ~~A~~ The method according to ~~any one of~~ claims 22 ~~to 25~~, wherein displaying one or more subsets of the data set includes:

using a composite view to view multiple attributes; and wherein

creating an additional attribute image ~~is created~~, wherein the additional attribute image ~~displaying~~ a union of a selected set of attributes.

Claim 27 (currently amended): A The method according to claim 26, wherein using a composite view further includes:

constructing an attribute matrix; and

selecting a highest value for each attribute value from the selected set of attributes.

Claim 28 (currently amended): A The method according to ~~any one of~~ claims 22 ~~to~~ 27, wherein displaying one or more subsets of the data set includes using a range filter, wherein using the range filter includes:

~~to~~ selecting regions on the data representation; and

filtering out nodes based on defined value ranges.

Claim 29 (currently amended): A The method according to ~~any one of~~ claims 22 ~~to~~ 28, wherein displaying one or more subsets of the data set includes using a zooming function, wherein using the zooming function includes:

making a selection of nodes to form a base reference of interest;

defining a set of data records from a second data set;

matching the second data set to the data representation;

flagging all records that are linked to the matched region; and

generating a second data representation using the flagged records.

Claim 30 (currently amended): A The method according to ~~any one of~~ claims 22 ~~to~~ 29, wherein displaying one or more subsets of the data set includes:

using visual scaling;

changing the minimum and maximum values used to calculate a color progression used to visualize at least one of the plurality of attributes; and

re-interpolating the active color ranges over the new valid range of attribute values.

Claim 31 (currently amended): A The method according to ~~any one of~~ claims 22 to 30, wherein displaying one or more subsets of the data set includes using a labeling engine, wherein using the labeling engine includes to:

- linking attribute columns in an input file to attributes in the data representation;
- selecting attributes from the input file to be used for labelling;
- determining with which row and column each row in the input file is associated;
- and
- placing labels on the data representation.

Claim 32 (currently amended): A The method according to ~~any one of~~ claims 22 to 31, wherein displaying one or more subsets of the data set includes using an advanced search function, wherein using the advanced search function includes to:

- reading a set of data records from a data source;
- matching attribute columns from the set of data records to attributes in the data representation; and
- displaying a list of all records that are associated with nodes that are part of the active selection on the data representation.

Claim 33 (currently amended): A The method according to ~~any one of~~ claims 22 to 32, wherein displaying one or more subsets of the data set includes using equal distance averaging (EDA), wherein using the equal distance averaging includes:

- finding the node vector,  $\mathbf{n}$ , in the data representation that most closely represents the input data vector,  $\mathbf{d}$ ; where  $\mathbf{n} = \arg \min_{K_{\langle r, c \rangle}} \left\{ \left\| K_{\langle r, c \rangle} - \mathbf{d} \right\|_p \right\}, \forall r \in [1, K_R], \forall c \in [1, K_C];$
- and
- replacing missing entries in  $\mathbf{d}$  with the corresponding entries from  $\mathbf{n}$ .

Claim 34 (currently amended): A The method according to claim 33, wherein using the equal distance averaging further includes:

building a list of the data representation nodes values,  $\overline{\mathbf{M}}$ , such that for each element  $\mathbf{m}$  of  $\overline{\mathbf{M}}$ ,  $\|\mathbf{m} - \mathbf{d}\|_p = 0$ ; wherein if  $\overline{\mathbf{M}}$  is empty, then replace each missing entry in  $\mathbf{d}$  with corresponding entries in  $\mathbf{n}$ ; and if  $\overline{\mathbf{M}}$  is not empty, then replace each missing entry in  $\mathbf{d}$  with the average value of the corresponding position of all the elements in  $\overline{\mathbf{M}}$ .

Claim 35 (currently amended): A The method according to ~~any one of claims 22 to 34~~, wherein the data representation is a knowledge filter.

Claim 36 (currently amended): A The method according to any of the preceding claims wherein the data representation includes a latent model of the data set.

Claim 37 (currently amended): A system for performing data analysis using neural networks, the system including:

~~one or more~~ a processors;

~~one or more~~ a memoryies coupled to the one or more processors; and

program instructions stored in the ~~one or more~~ memoryies, the ~~one or more~~ processors being operable to execute the program instructions, wherein the program instructions includeing processor executable code for executing the steps of:

generating a data representation using a data set, the data set including a plurality of attributes, wherein generating the data representation includes:

modifying the data set using a training algorithm, wherein the training algorithm includes growing the data set; and

performing convergence testing, wherein convergence testing checks for convergence of the training algorithm;; and ~~wherein~~

repeating the modificationing of the data set ~~is repeated~~ until convergence of the training algorithm occurs; and

displaying one or more subsets of the data set using the data representation.

Claim 38 (currently amended): ~~A~~ The system according to claim 37, wherein performing convergence testing includes testing condition  $q(t) < Q_e$ .

Claim 39 (currently amended): A ~~The~~ system according to claim 37 ~~or 38~~, wherein the data set includes a plurality of data set nodes, and wherein growing the data set includes:

finding  $K_q$  for each of the data set nodes, where  $K_q$  is the node with the highest average quantization error,  $\arg \max_q \left\{ \bar{q}(t)_{K_q} \right\}$  for each of the data set nodes,

where  $\bar{q}(t)_{K_q} = \frac{1}{t-1} \sum_{i=1}^{t-1} q(t)_{K_q}$  is the average quantization error for node  $q$ , where:

$$K_x = \arg \max_x \left\{ \|K_q - K_{\langle r(q)-1, c(q) \rangle} \|, \|K_q - K_{\langle r(q)+1, c(q) \rangle} \| \right\}$$

$$K_y = \arg \max_y \left\{ \|K_q - K_{\langle r(q), c(q)-1 \rangle} \|, \|K_q - K_{\langle r(q), c(q)+1 \rangle} \| \right\}$$

if  $\|K_y - K_c\| < \|K_x - K_c\|$  then

$$n_r = r(y) \text{ if } r(y) < r(c), \text{ else } n_r = r(c); \text{ and}$$

$$n_c = c(y);$$

$$\text{else } n_r = r(y); n_c = c(x) \text{ if } c(x) < c(c), \text{ else } n_c = c(c);$$

inserting a new row and column after row  $n_r$  and column  $n_c$ ; and

interpolating new attribute values for the newly inserted node vectors using:

$$K_{\langle r, n_c \rangle} = \left( K_{\langle r, n_c-1 \rangle} + K_{\langle r, n_c+1 \rangle} \right) \frac{\alpha}{2} \text{ and } K_{\langle n_r, c \rangle} = \left( K_{\langle n_r-1, c \rangle} + K_{\langle n_r+1, c \rangle} \right) \frac{\alpha}{2}, \text{ where } \alpha \in U(0,1).$$



Claim 40 (currently amended): A The system according to claim 37, ~~38, or 39~~, wherein the training algorithm further includes:

$t = t + 1;$

$\forall \mathbf{d} \in \overline{\mathbf{D}};$

if ( $t < 50$  or *afterGrow*)

$$\mathbf{d} = \arg \min_{\langle r, c \rangle, \forall r \in [1, F_R], \forall c \in [1, F_C]} \|\mathbf{d} - F_{\langle r, c \rangle}\|_{\rho}$$

*afterGrow* = *false*

else

$\mathbf{d} = \text{FindSCWS}(\mathbf{d})$

call function: *FindNeighborhoodPatterns*( $\overline{\phi}$ )

call function: *BatchUpdateMatchVectors*

$$q(t) = \frac{1}{\text{card}(\overline{\mathbf{D}})} \sum_i (\|\mathbf{d} - F_{\phi \mathbf{d}}\|_{\rho}); \text{ and}$$

if (*MayGrow*( $t$ ) and  $t < t_{\max}$ ), call function: *GrowKF*.

Claim 41 (currently amended): A The system according to ~~any one of~~ claims 37 to 40, wherein the program instructions ~~further include~~ for displaying one or more subsets of the data set further includes processor executable code for executing the steps of:

using a composite view to view multiple attributes; and wherein

creating an additional attribute image ~~is created~~, wherein the additional attribute image displaying a union of a selected set of attributes.

Claim 42 (currently amended): A The system according to ~~any one of~~ claims 37 to 41, wherein the program instructions further include processor executable code for executing the steps of:

constructing an attribute matrix; and

selecting a highest value for each attribute value from the selected set of attributes.

Claim 43 (currently amended): A The system according to ~~any one of~~ claims 37 to 42, wherein displaying one or more subsets of the data set includes using a range filter, ~~to~~ wherein the program instructions further include processor executable code for executing the steps of:

- selecting regions on the data representation; and
- filtering out nodes based on defined value ranges.

Claim 44 (currently amended): A The system according to ~~any one of~~ claims 37 to 43, wherein displaying one or more subsets of the data set includes using a zooming function, wherein the ~~wherein the~~ program instructions further include processor executable code for executing the steps of:

- making a selection of nodes to form a base reference of interest;
- defining a set of data records from a second data set;
- matching the second data set to the data representation;
- flagging all records that are linked to the matched region; and
- generating a second data representation using the flagged records.

Claim 45 (currently amended): A The system according to ~~any one of~~ claims 37 to 44, wherein displaying one or more subsets of the data set includes using visual scaling, wherein the ~~wherein the~~ program instructions further include processor executable code for executing the steps of:

- changing the minimum and maximum values used to calculate a color progression used to visualize at least one of the plurality of attributes; and
- re-interpolating the active color ranges over the new valid range of attribute values.

Claim 46 (currently amended): A The system according to ~~any one of~~ claims 37 to 45, wherein displaying one or more subsets of the data set includes using a labeling engine, wherein the program instructions further include processor executable code for executing the steps of:

- linking attribute columns in an input file to attributes in the data representation;
- selecting attributes from the input file to be used for labelling;
- determining with which row and column each row in the input file is associated;
- and
- placing labels on the data representation.

Claim 47 (currently amended): A The system according to ~~any one of~~ claims 37 to 46, wherein displaying one or more subsets of the data set includes using an advanced search engine, wherein the program instructions further include processor executable code for executing the steps of:

~~displaying one or more subsets of the data set includes using an advanced search function to:~~

- reading a set of data records from a data source;
- matching attribute columns from the set of data records to attributes in the data representation; and
- displaying a list of all records that are associated with nodes that are part of the active selection on the data representation.

Claim 48 (currently amended): A The system according to ~~any one of~~ claims 37 to 47, wherein displaying one or more subsets of the data set includes using equal distance averaging (EDA), wherein the program instructions further include processor executable code for executing the steps of:

finding the node vector,  $\mathbf{n}$ , in the data representation that most closely represents the input data vector,  $\mathbf{d}$ ; where  $\mathbf{n} = \arg \min_{K_{\langle r, c \rangle}} \left\{ \left\| K_{\langle r, c \rangle} - \mathbf{d} \right\|_{\rho} \right\}, \forall r \in [1, K_R], \forall c \in [1, K_C];$   
and

replacing missing entries in  $\mathbf{d}$  with the corresponding entries from  $\mathbf{n}$ .

Claim 49 (currently amended): A The system according to claim 48, wherein the program instructions further includes processor executable code for executing the steps of:

building a list of the data representation nodes values,  $\overline{\mathbf{M}}$ , such that for each element  $\mathbf{m}$  of  $\overline{\mathbf{M}}$ ,  $\left\| \mathbf{m} - \mathbf{d} \right\|_{\rho} = 0$ ; wherein if  $\overline{\mathbf{M}}$  is empty, then replace each missing entry in  $\mathbf{d}$  with corresponding entries in  $\mathbf{n}$ ; and if  $\overline{\mathbf{M}}$  is not empty, then replace each missing entry in  $\mathbf{d}$  with the average value of the corresponding position of all the elements in  $\overline{\mathbf{M}}$ .

Claim 50 (currently amended): A The system according to ~~any one of~~ claims 37 to 49, wherein the data representation is a knowledge filter.

Claim 51 (currently amended): A The system according to ~~any one of~~ claims 37 to 50, wherein the data representation includes a latent model of the data set.

Claim 52 (currently amended): A computer program product for computer data analysis using neural networks, the computer program product including:

computer-readable program code for generating a data representation using a data set, the data set including a plurality of attributes, wherein generating the data representation includes:

modifying the data set using a training algorithm, wherein the training algorithm includes growing the data set; ~~and~~

performing convergence testing, wherein convergence testing checks for convergence of the training algorithm;; ~~and wherein~~

repeating the training algorithm ~~is repeated~~ until convergence of the training algorithm occurs; and

computer-readable program code for displaying one or more subsets of the data set using the data representation.

Claim 53 (currently amended): A The computer program product according to claim 52, wherein the data set includes a plurality of data set nodes, and the computer program product further including computer-readable program code for growing the data set including:

finding  $K_q$  for each of the data set nodes, where  $K_q$  is the node with the highest average quantization error,  $\arg \max_q \{ \bar{q}(t)_{K_q} \}$  for each of the data set nodes,

where  $\bar{q}(t)_{K_q} = \frac{1}{t-1} \sum_{i=1}^{t-1} q(i)_{K_q}$  is the average quantization error for node  $q$ , where:

$$K_x = \arg \max_x \{ \|K_q - K_{\langle r(q)-1, c(q) \rangle} \|, \|K_q - K_{\langle r(q)+1, c(q) \rangle} \| \}$$

$$K_y = \arg \max_y \{ \|K_q - K_{\langle r(q), c(q)-1 \rangle} \|, \|K_q - K_{\langle r(q), c(q)+1 \rangle} \| \}$$

if  $\|K_y - K_c\| < \|K_x - K_c\|$  then

$n_r = r(y)$  if  $r(y) < r(c)$ , else  $n_r = r(c)$ ; and

$n_c = c(y)$ ;

else  $n_r = r(y)$ ;  $n_c = c(x)$  if  $c(x) < c(c)$ , else  $n_c = c(c)$ ;

inserting a new row and column after row  $n_r$  and column  $n_c$ ; and

interpolating new attribute values for the newly inserted node vectors using:

$$K_{\langle r, n_c \rangle} = (K_{\langle r, n_c-1 \rangle} + K_{\langle r, n_c+1 \rangle}) \frac{\alpha}{2} \text{ and } K_{\langle n_r, c \rangle} = (K_{\langle n_r-1, c \rangle} + K_{\langle n_r+1, c \rangle}) \frac{\alpha}{2}, \text{ where } \alpha \in U(0,1).$$

Claim 54 (currently amended): A The computer program product according to claim 52 or 53, wherein the data representation includes a latent model of the data set.

Claim 55 (currently amended): An apparatus for performing data analysis using neural networks, the apparatus including:

means for representing a data set, the data set including a plurality of attributes;

means for generating the representation means using the data set, wherein generating the representation means includes:

modifying the data set using a training algorithm, wherein the training algorithm includes growing the data set; and

performing convergence testing, wherein convergence testing checks for convergence of the training algorithm; and wherein

repeating the modificationing of the data set is ~~repeated~~ until convergence of the training algorithm occurs; and

means for displaying one or more subsets of the data set using the modified data representation.

Claim 56 (currently amended): ~~An~~ The apparatus according to claim 55, wherein the representation means includes a latent model of the data set.

Claim 57 (withdrawn): A method of computer data analysis using neural networks substantially as herein described with reference to the accompanying drawings.

Claim 58 (withdrawn): A system for performing data analysis using neural networks substantially as herein described with reference to the accompanying drawings.

Claim 59 (withdrawn): A computer program product for computer data analysis using neural networks substantially as herein described with reference to the accompanying drawings.

Claim 60 (withdrawn): An apparatus for performing data analysis using neural networks substantially as herein described with reference to the accompanying drawings.